

RMC150/151 DATASHEET

Two, Four, Six, and Eight Axis Motion Controllers

The RMC150/151 delivers high-performance motion control to hydraulic, electric servo, and pneumatic industrial applications. With powerful control modes—including dual-loop position-pressure algorithms—and connectivity to many transducer types, the RMC provides optimum control for a wide range of motion applications.

The RMC150/151 CPU module comes standard with Ethernet, supporting protocols such as EtherNet/IP, PROFINET, and Modbus/TCP, and is designed to integrate easily with your favorite PLCs, PCs, and HMsIs.

Equipped with excellent graphing features and easy-to-use wizards, the RMCTools software handles setup, programming, tuning, and diagnostics for both the RMC150 and RMC70 series controllers.

Flexible Multi-axis Capability

Modules can be “mixed and matched” to support up to 8 control axes for tightly synchronized motion, and additional reference axes up to a total of 16 control, reference, or virtual axes.

RMCTools Software

Setup, Programming,
Tuning and Diagnostics

USB,
Ethernet

Ethernet,
PROFIBUS-DP

HMs, PLCs, and PCs

Machine Control and
Operator Interface
Data Acquisition and
Plant Supervisory

±10V Analog

Actuators & Motors

Hydraulic & Pneumatic
Valves
Electric Motor Amplifiers
and Drives


Analog, SSI,
Quadrature,
MDT (PWM and
Start/Stop),
Resolver

Position & Pressure Feedback

Linear transducers
and rotary encoders
Pressure sensors
and load cells
Potentiometers



All RMC motion controllers are backed by a company legacy of more than 30 years of excellent product support. Responsive 24/7 customer service is just a telephone call away.



Industrial Applications

- ▲ Forest products
- ▲ Testing
- ▲ Metals
- ▲ Energy / Petrochemical
- ▲ Automotive
- ▲ Aerospace
- ▲ Plastics and rubber
- ▲ Entertainment
- ▲ Mining
- ▲ Petrochemical

More application notes at deltamotion.com/applications.


Communications

- ▲ **Ethernet** (10/100Mbps), built-in on CPU.
 - ▲ EtherNet/IP
 - ▲ PROFINET
 - ▲ Modbus/TCP
 - ▲ CSP (Allen-Bradley)
 - ▲ FINS (Omron)
 - ▲ Procedure Exist (Mitsubishi Q-series)
- ▲ **USB Port**
For use with the RMCTools software.
- ▲ **PROFIBUS-DP**

Feedback Types

- ▲ **Magnetostrictive Linear Displacement Transducer (MDT)**
RS-422 Start/Stop and PWM signals
- ▲ **Synchronous Serial Interface (SSI)**
Linear and single- or multi-turn rotary
- ▲ **Analog**
±10V and 4-20mA
- ▲ **Quadrature Encoder**
5V differential only (RS-422)
- ▲ **Resolver**
Wide range of frequencies and ratios

RMC150/151 DATASHEET



Part Numbers

Backplane sizes are 3, 4, 5, and 6 slots. Modules can be mixed and matched according to the table below.

Controller CPU. The CPU is always in slot 1 (second slot from left).

	Details
RMC150E Motion Control CPU (Includes Ethernet, RMCTools Software)	p. 5
RMC151E RMC150E with Dual-Loop Pressure/Force Control Option*	p. 5

(Multiple options possible)

Slots 2-5 Modules. Select 1-4 modules. $n = 1 - 4$.

M_n	Magnetostrictive Displacement Transducer (MDT) for Start/Stop or PWM signals: two inputs, two $\pm 10V$ outputs	p. 7
S_n	Synchronous Serial Interface (SSI) for linear and single- or multi-turn rotary: two inputs, two $\pm 10V$ outputs	p. 8
Q_n	Quadrature for 5V differential encoder signals: two inputs, two $\pm 10V$ outputs	p. 9
R_n	Resolver: two inputs, two $\pm 10V$ outputs	p. 10
H_n	Analog: four 16-bit $\pm 10V$ or 4-20mA inputs, two $\pm 10V$ outputs	p. 11
A_n	Analog: four 12-bit $\pm 10V$ or 4-20mA inputs	p. 12
G_n	Analog: two 16-bit $\pm 10V$ inputs, two $\pm 10V$ outputs	see note on p. 11
D_n	Discrete I/O: 8 discrete outputs, 18 discrete inputs, 24Vdc	p. 13
U_n	Universal reference: two 16-bit $\pm 10V$ or 4-20mA inputs, six discrete I/O, two high-speed quadrature or SSI channels	p. 14
BL_n	Blank slot cover allows for future expansion	

Slot 0 Modules

DI/O	Discrete I/O module, 8 discrete outputs, 18 discrete inputs, 24Vdc	p. 13
UI/O	Universal reference: two 16-bit $\pm 10V$ or 4-20mA inputs, six discrete I/O, two high-speed quadrature or SSI channels	p. 14
PROFI	PROFIBUS-DP communication	p. 16
Blank	Blank slot cover - no part number designation needed for blank cover in slot 0	

Options

HZ	Hazardous location designation Class I, Division 2, Groups A, B, C, D (not available for all modules)	p. 17
-----------	--	-------

* The Dual-Loop Pressure/Force Control Option is required only for dual-loop control, such as position-pressure, position-force, velocity-pressure, or velocity-force. It is not required for pressure-only control or force-only control. The Dual-Loop option also enables advanced control algorithms with two inputs per axis such as Active Damping or Acceleration control using pressure or accelerometer feedback.

Accessories and More

Voltage-to-Current Converters	p. 17
Cable Assemblies	p. 18
Terminal Blocks	p. 18
Mounting Dimensions	p. 19

Online Configuration Tool

Create your own RMC150 controller and request a quote!
Go to deltamotion.com and choose
Request a Quote Online.



Example Part Numbers

RMC150E-S2-Q2: 4 axes with SSI feedback, 4 axes with quadrature feedback, blank cover on the left-most slot

RMC151E-H4-PROFI: 8 axes with analog feedback (8 drive outputs and 16 analog inputs), PROFIBUS module, 8 axes dual-loop capable

RMC150E-M2-Q1-D1/I/O: 4 axes with MDT feedback, 2 axes with quadrature feedback, 2 discrete I/O modules, one of which is in slot 0

Company Profile

Delta Computer Systems, Inc. also doing business as Delta Motion, manufactures motion controllers and other industrial controls providing high-performance automation solutions to a wide range of industries.

DELTA MOTION

RMCTools Software

RMCTools is a powerful motion control software package for setting up, tuning, troubleshooting, programming, and controlling all features of Delta Motion's multi-axis RMC150/151 controllers from a PC. RMCTools also supports the RMC70 and RMC200 controllers.

Delta Motion's intuitive and easy-to-use RMCTools software features flexible User Programs with extensive commands and the ability to embed mathematical expressions. Setup and tuning wizards reduce startup times, and the graphical diagnostics tools speed up troubleshooting of the entire motion system. Extensive, context-sensitive help is included in RMCTools, giving you the information you need at your fingertips.

RMCTools is available for download from deltamotion.com.

Supported Operating Systems: Windows® 7/8.1/10/11

Communication Software

RMCLink ActiveX Control and .NET Assembly

RMCLink enables full monitoring and control of RMC150/151 motion controllers via Ethernet communications from custom applications on Windows®-based PCs. RMCLink supports numerous languages, such as Visual Basic, C++, C#, VBScript, VBA (Microsoft Excel®), or LabVIEW™.

RMCLink comes with fully-functioning sample projects to help you get up and running quickly. The help includes detailed walk-throughs and numerous code snippets.



RMCLink, with extensive examples, is available for download from deltamotion.com.

Microsoft, Windows, and Excel are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.

Instrument Driver for Use with LabVIEW

VIs created by Delta Motion for use with LabVIEW™ software provide full-fledged examples including plot uploading and trending. The VIs are available from the Instrument Driver portion of NI's website.

LabVIEW is a trademark of National Instruments. Neither Delta Motion, nor any software programs or other goods or services offered by Delta Motion, are affiliated with, endorsed by, or sponsored by National Instruments.



RMCTools Features

Delta Motion's powerful RMCTools software makes setup, tuning, and troubleshooting motion systems easier than ever.

Setup

▲ Wizards

Easy-to-use wizards include New Project, New Controller, Scale & Offset, and Autotuning.

▲ Full Parameter Set

Monitor all axis status registers and modify parameters.

Tuning and Diagnostics

▲ Plots

Plot any register in the RMC, up to 16 registers per plot, sampled as fine as the control loop resolution.

▲ Autotuning Wizard

Quickly and accurately tune your axes, using a slider bar to choose from a range of gains appropriate for your system.

▲ Event Log

Speed troubleshooting by recording events such as parameter changes, commands, errors, and communications.

▲ Program Monitor

Monitor User Program execution and variables.

Programming

▲ Commands

Issue commands directly from RMCTools. Use Shortcut Command Sets to quickly issue commands to speed the tuning process.

▲ User Programs


Easily create programs to issue sequences of commands.

▲ Program Triggers

Start user programs automatically based on user-defined events such as discrete inputs, error conditions, etc.

▲ Mathematical Expressions

Expressions provide flexible programming capability for advanced calculations and machine control sequences.



RMC150 Control Features

The RMC150 provides an extensive set of motion commands and programming capability for quick and easy yet flexible motion control for virtually every motion application.

Control Modes

Closed Loop Control

Full PID loop control with velocity, acceleration, and jerk feed forwards for precise synchronized motion. Directional gain factors support fluid power control.

Position Control

- ▲ Point-to-Point moves
- ▲ S-curves
- ▲ Speed at Position
- ▲ Gearing
- ▲ Cyclic Sinusoidal Motion
- ▲ Splines, Cams
- ▲ Rotary motion (incremental and absolute)

Velocity Control

- ▲ Velocity control with position feedback
- ▲ Velocity control with velocity feedback

Pressure and Force Control

- ▲ Pressure sensor, load cell, or differential force
- ▲ Linear or S-curve Ramps
- ▲ Gearing
- ▲ Cyclic Sinusoidal Profile
- ▲ Splines, Cams

Position-Pressure and Position-Force Control

- ▲ Transition seamlessly between position control and pressure or force control.
- ▲ Pressure or Force Limit – limit the pressure or force during a position or velocity move.

Active Damping

For high-performance control of pneumatics and difficult systems.

Open Loop Control

Seamless transition from open loop to closed loop. Ramp Control Output between two values, or ramp based on position for hard-to-control systems.

Quick Move

Move in open loop and stop in closed loop for fast, smooth motion with accurate stops.

Valve Linearization

For valves with a sharp knee or “kink” in the flow versus command signal diagram.

Custom Feedback

Control using any calculated value as feedback.

- ▲ Sum, difference, average, etc.
- ▲ Switch feedback on-the-fly
- ▲ Redundant feedback
- ▲ Feedback linearization

High-level programming

User Programs

Programs are easy-to-understand sequences of commands. Run multiple programs simultaneously to handle axis commands and machine control functions.

Program Triggers

Start user programs automatically based on user-defined events such as discrete inputs, error conditions, etc.

Variables

Recipes and other user parameters can be stored for use by user programs.

Mathematical Expressions

Expressions provide flexible programming capability for advanced calculations and machine control sequences.

Troubleshooting and Monitoring

Plots

Plot any register in the RMC70, up to 16 registers per plot, sampled down to the control loop resolution.

Event Log

Speeds troubleshooting by recording events such as parameter changes, commands, errors, and communications.

Fault Handling

Closed Loop stops

Ramp speed to zero at a specified rate and hold position.

Open Loop stops

Ramp output voltage to zero at a specified rate.

Multi-axis (group) stops

A fault on one axis halts multiple axes when configured as a group.

AutoStops

The response of axes to each fault type is easily configurable.

RMC150/151 DATASHEET

RMC150E and RMC151E CPUs

2-8 Axes Controllers


The RMC150E and RMC151E CPUs are capable of controlling up to 8 control axes plus additional reference axes. These CPUs provide an onboard Ethernet port, a USB port for connection to the RMCTools software, two 24Vdc discrete outputs, and two 12-24Vdc discrete inputs.

RMC150E – 8 Axes

Control 8 axes, built-in Ethernet, USB monitor port, 2 discrete inputs, 2 discrete outputs.

RMC151E – 8 Axes with Dual-Loop

RMC150E with dual-loop. Dual-loop is the ability to control two quantities—such as position and pressure—on the same axis. Notice that controlling only pressure or only force on an axis does not require the RMC151E.



RMC150E/RMC151E CPU Specifications

Motion Control

Control loop times 250 µs, 500 µs, 1 ms, 2 ms, or 4 ms

USB Monitor Port (for setup, programming, and maintenance only)

Connector USB "B" Receptacle

Data Rate Full-speed (12 Mbps)

Discrete Inputs (2)

Input type 12-24Vdc inputs; polarity independent

Logic polarity True "High"

Isolation 500Vac

Input "High" range 7 to 26.4Vdc, 3mA maximum

Input "Low" range 0 to 3.5Vdc, <1mA

Maximum propagation delay 160 µs

Discrete Outputs (2)

Output type Solid State Relays (SSR)

Isolation 500Vac

Rated voltage max ±30V (DC or peak AC voltage)

Maximum current ±75mA (±50mA for Class I Div 2)

Maximum propagation delay 2.0 ms

Logic 1 (True, On) Low impedance (50Ω maximum)

Logic 0 (False, Off) High impedance (<1µA leakage current at 250V)

Power

Voltage +24Vdc ±15%

Current 3 slots Typical 290mA, max 375mA

4 slots Typical 385mA, max 500mA

5 slots Typical 485mA, max 625mA

6 slots Typical 585mA, max 750mA

DC-DC converter isolation 500Vac

Mechanical

Mounting Symmetrical DIN 3 or panel-mount

Dimensions 3 slots 4.12 x 5.95 x 4.75 in (WxHxD) (10.5 x 15.0 x 12.1 cm)

(see pg. 19 for width increases by 1.0 in for each slot drawings)

6 slots 7.12 x 5.95 x 4.75 in (WxHxD) (18.1 x 15.0 x 12.1 cm)

Weight 3 slots 2 lb (0.9 kg) max

6 slots 3 lb (1.4 kg) max

DELTA MOTION

RMC150/151 DATASHEET



RMC150E/RMC151E CPU Specifications (continued)

Environment

Operating temperature	+32 to +140°F (0 to +60°C)
Storage temperature	-40 to +185°F (-40 to +85°C)
Agency compliance	UL, CUL. Optional: Class I, Division 2, see pg. 17

Ethernet Interface

Hardware interface	IEEE 802.3 for 100BASE-T (twisted pair)
Data Rate	10/100 Mbps
Duplex	Full/Half-Duplex
Features	Auto-negotiation, Auto-crossover (MDI/MDI-X)
Connector	RJ-45
Cable	CAT5, CAT5e or CAT6, UTP or STP

Ethernet Configuration

Configuration parameters	IP address, subnet mask, gateway address, enable/disable auto-negotiation
Configuration methods	BOOTP, DHCP, or static

Ethernet Protocol Support

Application Protocols (Call Delta Motion for the availability of other protocols)	EtherNet/IP, Modbus/TCP, PROFINET, CSP (DF1 over Ethernet), Omron FINS, Procedure Exist (Mitsubishi Q-series)
Framing protocol	Ethernet II
Internet protocol	IP (includes ICMP, ARP, and Address Collision Detection)

Transport protocols	TCP, UDP
---------------------	----------

Pin-out

Discrete I/O Connector

+In 0	General-purpose input 0
-In 0	
+In 1	General-purpose input 1
-In 1	
+Out 0	General-purpose output 0
-Out 0	
+Out 1	General-purpose output 1
-Out 1	

Power connector

+24V	Power for the entire controller
24 Cmn	Power common
Case	Protective earth ground

Ordering Information

The CPU part number is the first part of the entire controller part number. Specify RMC150E, or RMC151E for the dual-loop option.

For example, **RMC150E-M2**: RMC150 motion controller with 4 axes of MDT position control.

DELTA MOTION



MDT Module


Two Axes, Magnetostrictive Linear Displacement Transducers

The two-axis MDT module interfaces to magnetostrictive linear displacement transducers (MDTs) with Start/Stop or Pulse Width Modulated (PWM) outputs. These absolute-position transducers are especially well suited for hydraulic applications because of their non-contact design, robustness, modularity, and resistance to contaminants.

Magnetostrictive linear displacement transducers with the SSI interface provide higher resolution than Start/Stop or PWM outputs and are supported by the RMC SSI module.

Features:

- Two axes of MDT feedback per module
- Up to 0.001 in (25.4 µm) resolution using Start/Stop
- Up to 0.0001 in (2.54 µm) resolution using PWM transducers with multiple recirculations
- Supports internal transducer recirculations
- Transducer length up to 398 in (10.1 m) (4 ms loop time)
- Differential (recommended) or single-ended interface
- Two isolated, ±10V, 12-bit drive outputs per module
- Current output up to ±200mA with VC2124 converter option



MDT Specifications

Start/Stop and PWM Interface

Axes	Two per module
Return inputs	Two RS-422 differential
Interrogation outputs	Two RS-422 differential (External interrogation required)
ESD protection	15kV Electrostatic Discharge (ESD) protection
Resolution	0.001 in (25.4 µm) Start/Stop, 0.0001 in (2.54 µm) PWM
Count rate	120MHz

Drive Interface

Outputs	Two ±10V, 5mA maximum, 12-bit DAC
Isolation	500Vac
Current Output Accessory	VC2124 voltage-to-current converter output range is adjustable from ±10mA to ±200mA in 10mA steps

Environment

Operating temperature	+32 to +140°F (0 to +60°C)
Storage temperature	-40 to +185°F (-40 to +85°C)
Agency compliance	UL, CUL. Optional: Class I, Division 2, see pg. 17

MDT Pin-out

MDT 0 Connector	
+Int 0	+ Interrogation
-Int 0	- Interrogation
MDT Cmn	Transducer Common
+Ret 0	+ Return
-Ret 0	- Return
Case	Chassis Ground (shield)

MDT 1 Connector	
+Int 1	+ Interrogation
-Int 1	- Interrogation
MDT Cmn	Transducer Common
+Ret 1	+ Return
-Ret 1	- Return
Case	Chassis Ground (shield)

Drive Connector	
Drv 0	±10V Drive Output
Drv Cmn	Drive Common
Drv 1	±10V Drive Output
Case	Chassis Ground (shield)

MDT Ordering Information

To specify an MDT interface module, insert **-Mn** into the part number, where **n** indicates the number of modules. Up to four MDT modules can be ordered in a single RMC unit. The MDT module can be used in slots 2-5. Refer to the SSI module for Magnetostrictive LDTs with a Synchronous Serial Interface (SSI) output.

For example, **RMC150E-M2-A1**: 4 axes of MDT position control and 4 analog inputs.



SSI Module

Two Axes, Synchronous Serial Interface


The two-axis SSI module interfaces to transducers with the Synchronous Serial Interface (SSI) output. Many types of transducers are available with SSI, including magnetostrictive linear displacement transducers, absolute encoders, and laser measuring devices.

SSI has several advantages over other interfaces:

- Higher noise immunity
- Absolute positions
- Available on a wide variety of transducers
- Many SSI devices offer higher precision.
For example, magnetostrictive LDTs offer higher resolutions with SSI interface than for other interface types, such as Start/Stop, PWM, voltage, or current.

Features:

- Two axes of SSI feedback per module
- Binary or gray code
- 8 to 31 data bits
- Differential RS-422 SSI interface
- Two isolated, $\pm 10V$, 12-bit drive outputs per module
- Current output up to $\pm 200mA$ with VC2124 converter option



SSI Specifications

SSI Interface

Axes	Two per module
Data inputs	Two RS-422 differential, 150Ω input impedance
Clock outputs	Two RS-422 differential
Clock frequency	User-selectable 230kHz or 921kHz
Cable type	Twisted pair, shielded, low capacitance communication cable
Cable length maximum	Transducer dependent (approx. 300-600 ft)
ESD protection	15kV Electrostatic Discharge (ESD) protection
Resolution	Transducer dependent (up to $2 \mu m$ or approximately 0.00008 in for magnetostrictive LDTs)
Count encoding	Binary or Gray Code
Data bits	8 to 31-bits

Drive Interface

Outputs	Two $\pm 10V$, 5mA maximum, 12-bit DAC
Isolation	500Vac
Current Output Accessory	VC2124 voltage-to-current converter output range is adjustable from $\pm 10mA$ to $\pm 20mA$ in 10mA steps

Environment

Operating temperature	+32 to +140°F (0 to +60°C)
Storage temperature	-40 to +185°F (-40 to +85°C)
Agency compliance	UL, CUL. Optional: Class I, Division 2, see pg. 17

SSI Pin-out

SSI 0 Connector	
+Clk 0	+ Clock Output
-Clk 0	- Clock Output
SSI Cmn	Transducer Common
+Dat 0	+ Data Input
-Dat 0	- Data Input
Case	Chassis Ground (shield)

SSI 1 Connector	
+Clk 1	+ Clock Output
-Clk 1	- Clock Output
SSI Cmn	Transducer Common
+Dat 1	+ Data Input
-Dat 1	- Data Input
Case	Chassis Ground (shield)

Drive Connector	
Drv 0	$\pm 10V$ Drive Output
Drv Cmn	Drive Common
Drv 1	$\pm 10V$ Drive Output
Case	Chassis Ground (shield)

SSI Ordering Information

To specify an SSI interface module, insert **-S_n** into the part number, where *n* indicates the number of modules. Up to four SSI modules can be ordered in a single RMC unit. The SSI module can be used in slots 2-5.

For example, **RMC150E-S3-A1**: 6 axes of SSI position control and 4 analog inputs.



Quadrature Module

Two Axes, 5V differential (RS-422) A, B, and Z

The two-axis Quadrature module interfaces to linear and rotary transducers and encoders with 5V differential (RS-422) A, B, and Z outputs. Many types of transducers and encoders are available with quadrature outputs.

In addition to A, B, and Z (index) inputs, each axis includes a high-speed homing input, a drive enable output, a drive fault input, and two high-speed inputs for limit switches or high-speed position latching.

Features:

- Two axes of quadrature feedback per module
- 4,000,000 counts per second
- High-speed inputs: home, position latch, travel limits
- Digital noise filters on all inputs
- All discrete inputs are isolated
- Drive fault inputs, Drive enable outputs
- Two isolated, $\pm 10V$, 14-bit drive outputs per module
- Current output to $\pm 200mA$ with VC2124 converter option



Quadrature Specifications

Inputs and Outputs

Axes	Two per module
Inputs	Two 5V differential (RS-422), 215Ω input impedance, A, B, and Z
ESD Protection	15kV Electrostatic Discharge (ESD) Protection
Maximum Encoder Frequency	4,000,000 counts/s
Fault Inputs, Home Inputs, and high-speed Limit or Registration Inputs	Input "High" range: 3.2 to 26.4Vdc, 3.5mA min., 10mA max. Input "Low" range: 0 to 2Vdc, < 1mA Max input voltage: 26.4V, 500Vac isolation, compatible with most limit switches, TTL, and CMOS outputs
Home input response time	50 μ s
Index (Z) input response time	125 ns
Drive Enable output	Solid State relay, 50Ω , 30V, 75mA (50mA for Class I, Div 2), 1.5 ms, 500Vac isolation

Drive Interface

Outputs	Two $\pm 10V$, 5mA maximum, 14-bits DAC
Isolation	500Vac
Current Output Accessory	VC2124 voltage-to-current converter output range is adjustable from $\pm 10mA$ to $\pm 200mA$ in 10mA steps

Environment

Operating temperature	+32 to +140°F (0 to +60°C)
Storage temperature	-40 to +185°F (-40 to +85°C)
Agency compliance	UL, CUL. Optional: Class I, Division 2, see pg. 17

Quadrature Pin-out

Pin	Function
1	A-
2	A+
3	B-
4	B+
5	No connection
6	Registration X / Neg Limit -
7	Registration X / Neg Limit +
8	Registration Y / Pos Limit -

Pin	Function
9	Registration Y / Pos Limit +
10	No connection
11	No connection
12	$\pm 10V$ Drive Output
13	Drive Output Common
14	Z- Index from encoder
15	Z+ Index from encoder
16	Encoder Common

Pin	Function
17	No connection
18	Home Input -
19	Home Input +
20	Fault Input -
21	Fault Input +
22	No connection
23	No connection
24	Enable Output
25	Enable Output

Quadrature Ordering Information

To specify a Quadrature module, insert **-Qn** into the part number, where **n** indicates the number of modules. Up to four Quadrature modules can be ordered in a single RMC unit. The Quadrature module can be used in slots 2-5.

For example, **RMC150E-Q2-A1**: 4 axes of quadrature position control and 4 analog inputs.




Resolver Module

Two Axes, Resolvers 800Hz to 5kHz, ratios 0.42 to 1.41

The two-axis Resolver module interfaces to resolvers. These single-turn absolute-position transducers are well-suited for hazardous and harsh environments due to the simplicity and robustness of the transducer construction.

Features:

- Two axes of resolver feedback per module
- 14 or 16-bit resolution
- Reference frequency from 800Hz to 5kHz
- Resolver Transformation Ratios from 0.42 to 1.41
- Custom frequency and transformation ratios options available – contact Delta Motion
- Two isolated, $\pm 10V$, 14-bit drive outputs per module
- Current output up to $\pm 200mA$ with VC2124 converter option



Resolver Specifications

Inputs

Axes	Two per module
Reference Frequency	800Hz to 5kHz
Reference Output Voltage	1.41 to 4.8V RMS
Reference Output Current	28mA max.
Resolver Transformation Ratio (SINMAX/Reference)	0.42 to 1.41
Resolution	14 or 16-bits
Maximum Speed	3000 RPM at 14-bits and 600 RPM at 16-bits
Maximum Acceleration	1200 RPS per second at 14-bits, 60 RPS per second at 16-bits
Accuracy	4 Minutes +1 LSB

Drive Interface

Outputs	Two $\pm 10V$, 5mA maximum, 14-bit DAC
Isolation	500Vac
Current Output Accessory	VC2124 voltage-to-current converter output range is adjustable from $\pm 10mA$ to $\pm 200mA$ in 10mA steps

Environment

Operating temperature	+32 to +140°F (0 to +60°C)
Storage temperature	-40 to +185°F (-40 to +85°C)
Agency compliance	UL, CUL. Optional: Class I, Division 2, see pg. 17

Resolver Pin-out

Resolver 0 Connector

R1 0	Reference Output +
Ref In 0	Reference In (normally not used)
R3 0	Reference Output –
S1 0	Sine Input +
S3 0	Sine Input –
S2 0	Cosine Input +
S4 0	Cosine Input –
Case	Chassis ground (shield)

Resolver 1 Connector

R1 1	Reference Output +
Ref In 1	Reference In (normally not used)
R3 1	Reference Output –
S1 1	Sine Input +
S3 1	Sine Input –
S2 1	Cosine Input +
S4 1	Cosine Input –
Case	Chassis ground (shield)

Drive Connector

Drv 0	$\pm 10V$ Drive Output
Drv Cmn	Drive Common
Drv 1	$\pm 10V$ Drive Output
Case	Chassis Ground (shield)

Resolver Ordering Information

To specify a Resolver module, insert **-Rn** into the part number, where **n** indicates the number of modules. Up to four Resolver modules can be ordered in a single RMC unit. The Resolver module can be used in slots 2-5.

For example, **RMC150E-R2**: 4 axes of resolver position control.




Analog (H) Module

Two Axes, Four Voltage or Current Inputs

The two-axis H module interfaces to $\pm 10V$, $\pm 5V$, and 4-20mA transducers. This module includes two drive outputs and four 16-bit inputs for controlling position, velocity, pressure, or force. The four inputs provide flexibility in your system and can be used for such things as reference inputs (e.g. a joystick input), connecting to two pressure transducers to control the resultant force on a hydraulic cylinder, or for dual-loop position-pressure or position-force control (requires the RMC151E CPU).

Features:

- Four isolated 16-bit inputs
- 8 times oversampling
- $\pm 10 V$, $\pm 5V$, and 4-20mA input ranges
- $+10 V$ exciter output
- Two isolated, $\pm 10V$, 12-bit drive outputs per module
- Current output up to $\pm 200mA$ with VC2124 converter option



Analog Specifications

Inputs	
Inputs	Four 16-bit differential
Isolation	500Vac
Overshoot protection	$\pm 40V$
Input ranges	$\pm 10V$, $\pm 5V$, 4-20mA (each input independently configurable)
Input impedance	$1M\Omega$
Input filter slew rate	25V/ms
Oversampling	8 times per control loop
Offset drift with temperature	0.2 LSB/ $^{\circ}C$ typical ($\pm 10 V$ range)
Gain drift with temperature	20 ppm/ $^{\circ}C$ typical ($\pm 10 V$ range)
Non-linearity	12 LSB (counts) typical ($\pm 10 V$ range)
Exciter output	10Vdc $\pm 2\%$, 8mA (for use with potentiometers only)
Drive Interface	
Outputs	Two $\pm 10V$, 5mA maximum, 12-bit DAC
Isolation	500Vac
Current Output Accessory	VC2124 voltage-to-current converter output range is adjustable from $\pm 10mA$ to $\pm 200mA$ in 10mA steps
Environment	
Operating temperature	+32 to +140 $^{\circ}F$ (0 to +60 $^{\circ}C$)
Storage temperature	-40 to +185 $^{\circ}F$ (-40 to +85 $^{\circ}C$)
Agency compliance	UL, CUL. Optional: Class I, Division 2, see pg. 17

Note: Analog (G) Module

The Analog (G) module has two $\pm 10V$ inputs and two $\pm 10V$ drive outputs.

Delta Motion recommends using the H module instead of the G module. The similarly-priced H module has four analog inputs instead of two and supports 4-20mA feedback.

For detailed specifications on the G module, refer to the RMC100 datasheets at deltamotion.com/dloads.

Analog Pin-out

Inputs 0&1 Connector	
+In 0	Differential analog input 0+
Res 0	Connect to +In 0 for 4-20mA
-In 0	Differential analog input 0-
+In 1	Differential analog input 1+
Res 1	Connect to +In 1 for 4-20mA
-In 1	Differential analog input 1-
Input Cmn	Analog common (Isolated)
+10Vdc	+10Vdc output for use with potentiometers only
Exciter Out	

Inputs 2&3 Connector	
+In 2	Differential analog input 2+
Res 2	Connect to +In 2 for 4-20mA
-In 2	Differential analog input 2-
+In 3	Differential analog input 3+
Res 3	Connect to +In 3 for 4-20mA
-In 3	Differential analog input 3-
Input Cmn	Analog common (Isolated)
Case	Chassis Ground (shield)

Drive Connector	
Drv 0	$\pm 10V$ Drive Output
Drv Cmn	Drive Common
Drv 1	$\pm 10V$ Drive Output
Case	Chassis Ground (shield)

Analog Ordering Information

To specify an H module, insert **-Hn** into the part number, where **n** indicates the number of modules. Up to four H modules can be ordered in a single RMC unit. The H module can be used in slots 2-5.

For example, **RMC150E-H2-DI/O**: Two H modules and one discrete I/O module.

Analog (A) Module



Four Voltage or Current Inputs

The A module provides four 12-bit analog inputs, individually configurable as $\pm 10V$, $\pm 5V$, or 4-20mA. The inputs provide flexibility in designing your system and are typically used in the following applications:

- Dual-loop position-pressure or position-force control. The A module is typically used to provide the analog inputs for the pressure transducers or force load cells.
- Reference inputs, such as joystick inputs.
- Differential force input from two pressure transducers on a hydraulic cylinder.

Features:

- Four isolated 12-bit inputs
- 8 times oversampling
- $\pm 10V$, $\pm 5V$, and 4-20mA input ranges
- $+10V$ exciter output



Analog Specifications

Inputs	
Inputs	Four 12-bit differential
Isolation	500Vac
Overshoot protection	$\pm 40V$
Input ranges	$\pm 10V$, $\pm 5V$, 4-20mA (each input independently configurable)
Input impedance	$1M\Omega$
Input filter slew rate	25V/ms
Oversampling	8 times per control loop
Offset drift with temperature	0.01 LSB/ $^{\circ}C$ typical ($\pm 10V$ range)
Gain drift with temperature	20 ppm/ $^{\circ}C$ typical ($\pm 10V$ range)
Non-linearity	1 LSB (count) typical ($\pm 10V$ range)
Exciter output	10Vdc $\pm 2\%$, 8mA (for use with potentiometers only)
Environment	
Operating temperature	+32 to +140 $^{\circ}F$ (0 to +60 $^{\circ}C$)
Storage temperature	-40 to +185 $^{\circ}F$ (-40 to +85 $^{\circ}C$)
Agency compliance	UL, CUL. Optional: Class I, Division 2, see pg. 17

Analog Pin-out

Inputs 0&1 Connector	
+In 0	Differential analog input 0+
Res 0	Connect to +In 0 for 4-20mA
-In 0	Differential analog input 0-
+In 1	Differential analog input 1+
Res 1	Connect to +In 1 for 4-20mA
-In 1	Differential analog input 1-
Input Cmn	Analog common (Isolated)
+10Vdc	+10Vdc output for use with potentiometers only

Inputs 2&3 Connector	
+In 2	Differential analog input 2+
Res 2	Connect to +In 2 for 4-20mA
-In 2	Differential analog input 2-
+In 3	Differential analog input 3+
Res 3	Connect to +In 3 for 4-20mA
-In 3	Differential analog input 3-
Input Cmn	Analog common (Isolated)
Case	Chassis Ground (shield)

Analog Ordering Information

To specify an A module, insert **-An** into the part number, where **n** indicates the number of modules. Up to four A modules can be ordered in a single RMC unit (four is rare, as the RMC would have no drive outputs for control). The A module can be used in slots 2-5.


For example, **RMC150E-M2-A1-DI/O**: 4 axes of MDT position control, 4 analog inputs, and one discrete I/O module.



Discrete I/O Module

18 Discrete Inputs, 8 Discrete Outputs

The Discrete I/O module provides 8 discrete outputs and 18 discrete inputs, supporting 5 V to 24 V signal levels. The discrete I/O can be used for many tasks, for example, starting motion sequences, providing interlocks, starting external events, simple communications, and more.



Discrete I/O Specifications

Discrete Inputs

Inputs	18, compatible with signal levels from 5V to 24V
Input Characteristics	5-24Vdc, sinking (requires sourcing driver)
Logic Polarity	True high
Isolation	500 Vac
Input "High" Range	3 to 26.4Vdc 3.2mA minimum, 10mA maximum
Input "Low" Range	0 to 2Vdc < 1mA
Filtering	Inputs 0-15: 500 µs Inputs 16-17: 250 µs
Maximum Propagation Delay	100 µs + filtering

Outputs

Outputs	8, Solid State Relay
Logic polarity	True On
Isolation	500Vac
Maximum voltage	±30V (DC or peak AC voltage rating of SSR)
Maximum current	±75mA (±50mA for Class I, Div 2)
Maximum propagation delay	1.5 ms
Logic 1 (True, On)	Low impedance (50Ω maximum)
Logic 0 (False, Off)	High impedance (<1µA leakage current at 250V)

Environment

Operating temperature	+32 to +140°F (0 to +60°C)
Storage temperature	-40 to +185°F (-40 to +85°C)
Agency compliance	UL, CUL. Optional: Class I, Division 2, see pg. 17

Discrete I/O Pin-out

Discrete Outputs	
0-7	General Outputs 0-7
Output Cmn	Common (high or low side)

Discrete Inputs	
0-17	General Inputs 0-17
Input Cmn	Common (must be low side)


Discrete I/O Ordering Information

The part number depends on the slot in which the Discrete I/O module is installed. The Discrete I/O module for slot 0 is not interchangeable with the Discrete I/O module for slots 2-5.

Slot 0: Append **-DI/O** to the part number.

SLOTS 2-5: Insert **-Dn** to the part number, where **n** indicates the number of modules.

For example, **RMC150E-M2-D1-DI/O**: 4 axes of MDT position control and 2 discrete I/O modules, one of which is in slot 0.



Universal I/O Module

2 Analog Inputs, 6 Discrete I/O, 2 Quadrature/SSI Channels

The Universal Input/Output module provides two analog inputs, six discrete inputs/outputs, and two high-speed channels that can be configured for quadrature inputs, SSI inputs, or even inter-controller communications for synchronizing axes between RMCs.

Analog Input Features:

- Two 16-bit analog inputs, ±10V or 4-20mA

Discrete I/O Features:

- Six I/O, individually configurable as input or output
- Inputs: 12 to 24Vdc, sinking or sourcing
- Outputs: Solid state relay, 75mA
- Inputs 0 and 1 can be used as high-speed registration inputs in conjunction with the quadrature inputs.

High-Speed Channel Features

Each of the two RS-422 channels is independently configurable as Quadrature or SSI.

Quadrature Channels


Each high-speed channel can be configured as a quadrature.

- A and B quadrature inputs
- Requires 5V differential (RS-422) signals
- Discrete inputs 0 and 1 can be used as high-speed registration or homing inputs in conjunction with quadrature inputs 0 and 1, respectively.

SSI Channels

Each high-speed channel can be configured to do the following SSI tasks:

- **Receive SSI Input from a Transducer**
This is a standard SSI input for obtaining data from an SSI transducer or encoder.
- **Send Data Out Via SSI (Slave)**
The SSI channel behaves as a transducer or encoder and will return data to the requesting master.
- **Synchronize Multiple RMCs to One Transducer**
The SSI channel can monitor the data that another RMC is receiving from an SSI device. This makes it possible to synchronize multiple RMCs to one SSI transducer.
- **Communicate between RMCs**
The SSI channels can exchange data between RMCs every loop time of the controller, providing the ability to tightly synchronize axes between RMCs.



Specifications

See the next page.

Universal I/O Pin-out

Analog In Connector	
+In 0	Differential analog input 0+
Jmpr for 4-20mA	Connect to +In0 for 4-20mA
-In 0	Differential analog input 0-
Input Cmn	Analog common (Isolated)
+In 1	Differential analog input 1+
Jmpr for 4-20 mA	Connect to +In0 for 4-20mA
-In 1	Differential analog input 1-
Input Cmn	Analog common (Isolated)
Case	Chassis Ground (shield)

DI/O Connector	
Out Cmn	Common to one side of all outputs
I/O 0/RO	Input or Output
I/O 1/R1	Input or Output
I/O 2	Input or Output
I/O 3	Input or Output
I/O 4	Input or Output
I/O 5	Input or Output
In Cmn	Common to one side of all inputs
Case	Chassis Ground (shield)

Quad/SSI Connector	
+A0/Clk0	Channel 0: A Input, Clock Output, or Clock Input
-A0/Clk0	
+B0/Dat0	Channel 0: B Input, Data Input, or Data Output
-B0/Dat0	
Q/S Cmn	Quad/SSI Common
+A1/Clk1	Channel 1: A Input, Clock Output, or Clock Input
-A1/Clk1	
+B1/Dat1	Channel 1: B Input, Data Input, or Data Output
-B1/Dat1	
Case	Chassis Ground (shield)

Universal I/O Ordering Information


The part number depends on the slot in which the Universal I/O module is installed. The Universal I/O module for slot 0 is not interchangeable with the Universal I/O module for slots 2-5.

Slot 0: Append -UI/O to the part number.

Slots 2-5: Insert -Un to the part number, where *n* indicates the number of modules.

For example, **RMC150E-M2-UI/O:** 4 axes of MDT position control and one Universal I/O module in slot 0.

RMC150/151 DATASHEET



Universal I/O Specifications

Analog Inputs

Inputs	Two 16-bit differential inputs
Isolation	500Vac
Overshoot protection	±40V
Input ranges	±10V and 4-20mA (each input independently configurable)
Input impedance	5MΩ
Input filter frequency	1.2kHz
Input filter slew rate	25V/ms
Sampling rate	60kHz
Offset drift with temperature	0.2 LSB/°C typical
Gain drift with temperature	20 ppm/°C typical
Non-linearity	12 LSB (counts) typical over the full 16-bit range

Discrete I/O – General

Discrete I/O points	6; Each is individually configurable as input or output
Isolation	500Vac
Discrete I/O – Inputs	
Input characteristics	12-24Vdc, sinking or sourcing
Logic polarity	True "high"
Input "high" range	7 to 26.4Vdc (polarity independent), 3mA maximum
Input "low" range	0 to 3.5Vdc (polarity independent), <1mA
Maximum propagation delay	160 µs + filtering
Filtering	50 µs (value stable for 7 samples @ 8 µs interval)
Registration	Inputs 0 and 1 can be used as high-speed registration inputs in conjunction with the quadrature inputs. For this use, filtering can be set to 100ns (max propagation delay is still 160 µs).

Discrete I/O – Outputs

Output characteristics	Solid State Relay
Logic polarity	True On
Maximum voltage	±30V (DC or peak AC rating of SSR)
Maximum current	±75mA
Maximum propagation delay	2.0 ms
Logic 1 (True, On)	Low impedance (25Ω typ, 50Ω max)
Logic 0 (False, Off)	High impedance (<1µA at 250V)
Environment	
Operating temperature	+32 to +140°F (0 to +60°C)
Storage temperature	-40 to +185°F (-40 to +85°C)
Agency compliance	Contact Delta Motion

High-Speed Channels

Channels	2, independently configurable
Transducer types	MDT with SSI output, single- or multi-turn absolute SSI encoders, and quadrature encoders.
	Note: Linear MDTs with SSI output should be of the synchronized type. Non-synchronized is not well-suited for motion control.
Modes	Quadrature input – ±A and ±B inputs SSI Standard input – for interfacing to transducers and encoders SSI Monitor input – for monitoring SSI communication on another device SSI Slave output – emulates a transducer SSI Master output – for sending data to another controller
Input type (Data/Clock/Quad)	RS-422 (5V differential) (Single-ended encoders not supported due to low noise immunity)
Output type (Clock/Data)	RS-422 (5V differential)
Clock frequency	250kHz, 500kHz, or 971kHz, user-selectable
Resolution	Transducer dependent (typically down to 2µm or approximately 0.00008" for MDTs)
SSI count encoding	Binary or Gray code
SSI count data length	8 to 32-bits
Termination	215Ω – user-selectable on all inputs
Registration	Discrete inputs 0 and 1 can be used as high-speed registration for channels 0 and 1 respectively.
Registration response time	160 µs
Max encoder frequency	8,000,000 quadrature counts per second
Maximum cable length	1000 ft (Low capacitance, shielded, twisted pair computer communication cable)
Electrostatic discharge (ESD) protection	15kV (human body model)
Isolation	500Vac



PROFIBUS Module

PROFIBUS-DP Communications

The RMC150 PROFIBUS-DP module supports data rates up to 12 Mbaud, which permits the high-speed transfer of any data to and from the RMC, including position commands, parameters, and status information.

The RMC's PROFIBUS interface gives the flexibility of several modes, including I/O Modes with in/out data of 4, 8, 16, or 32 registers. Select the mode that best fits your application and PROFIBUS master's capabilities.

With the PROFIBUS module installed, the RMC150/151 supports simultaneous Ethernet and PROFIBUS communications.



PROFIBUS Specifications

PROFIBUS-DP Interface

Data Rate	9.6kbaud up to 12Mbaud
Isolation	2500Vac
Product Identifier Number	0x0AC6
Features Supported	Sync Mode, Freeze Mode, Auto-baud rate detect
Valid Station Addresses	0-126 (set by software or Set Slave Address function)
Connector	Standard PROFIBUS-DP DB-9 (use termination in cable connectors as per PROFIBUS specification)

Environment

Operating temperature	+32 to +140°F (0 to +60°C)
Storage temperature	-40 to +185°F (-40 to +85°C)
Agency compliance	UL, CUL. Optional: Class I, Division 2, see pg. 17

PROFIBUS Ordering Information

To specify a PROFIBUS interface module, append **-PROFI** to the part number. The PROFIBUS module can only be used in slot 0.

For example, **RMC150E-M2-PROFI**: 4 axes of MDT position control and PROFIBUS communications.



Class I Division 2 Compliance

Hazardous location designation Class I, Division 2, Groups A, B, C, and D is available for the RMC150E, excluding the G and UI/O modules.

- Products marked "Class I Division 2, Group A, B, C, D" are suitable for use in Class I Division 2, Groups A, B, C, and D hazardous locations and nonhazardous locations only.
- **WARNING—EXPLOSION HAZARD—DO NOT DISCONNECT EQUIPMENT WHILE THE CIRCUIT IS LIVE OR UNLESS THE AREA IS KNOWN TO BE FREE OF IGNITABLE CONCENTRATIONS.**
- **WARNING—EXPLOSION HAZARD—SUBSTITUTION OF ANY COMPONENT MAY IMPAIR SUITABILITY FOR CLASS I, DIVISION 2.**
- Maximum surrounding air temperature of 60° C.
- The RMC150E USB port is intended for configuration, programming, and troubleshooting purposes only. It should not be connected during normal operation.
- Wire gauge, screw clamp torque, and wire type requirements are listed in the RMC Startup Guide and RMCTools help.


Class I Division 2 Ordering Information

To specify Class I, Division 2, append “-HZ” to the entire RMC part number. Class I Division 2 compliance is not available for RMC configurations with the G and UI/O modules.

Voltage-to Current Converters

Delta Motion's voltage-to-current converters are designed for converting a voltage drive output to a current drive output to control a servo valve. Delta Motion offers several voltage-to-current converters to fit your needs. The maximum output current is adjustable in increments of 10 mA up to the maximum output current range.

Part Number	Description	Output Current Range*	Power Supply
VC2124	2-channel voltage-to-current converter	±100mA per channel	24Vdc
VC2100	2-channel voltage-to-current converter	±100mA per channel	±15Vdc
VC2100-HS	2-channel voltage-to-current converter – high speed**	±100mA per channel	±15Vdc




VC2124

VC2100

VC2100-HS

* Channels can be connected in parallel to provide higher currents. For example, two ±100 mA channels connected in parallel will provide ±200 mA.

**Most hydraulic control applications do not require a high-speed converter.



Cable Assemblies

Delta Motion provides cable assemblies for certain products. The table below lists the available cables:

Cable Part No	Length	Cable Description
RMC-CB-QUAD-01-06	6 ft.	
RMC-CB-QUAD-01-10	10 ft.	
RMC-CB-QUAD-01-15	15 ft.	
RMC-CB-QUAD-01-20	20 ft.	Cable for Quadrature module. 1 DB25 to 3 individual pig-tailed cables for drive, encoder, and limits.

Custom lengths are available per request. A drawing of RMC-CB-QUAD-01-xx is available on the Downloads page of Delta Motion's website at deltamotion.com/dloads.




Terminal Blocks

All RMCs ship with connectors. Connectors are available from Delta Motion. The table below lists the available connectors. These parts are also available from connector manufacturers Amphenol Pcd or WECO using these part numbers.


Connector Part No	Connector Description	For Modules
121-C-111/04 (WECO)	RMC100/150 4-pin Terminal Block	M, S, H, G, R
121-C-111/06 (WECO)	RMC100/150 6-pin Terminal Block	M, S
121-C-111/08 (WECO)	RMC100/150 8-pin Terminal Block	H, A, G, R
121-C-111/11 (WECO)	RMC100/150 11-pin Terminal Block	RMC150/151E
ELVP09100 (Amphenol Pcd)	RMC100/150 9-pin Terminal Block	DI/O, UI/O
ELVP19100 (Amphenol Pcd)	RMC100/150 19-pin Terminal Block	DI/O, UI/O






Mounting Dimensions

The width of the RMC depends on the number of slots in the backplane.
 CAD drawings of the RMC are available at deltamotion.com/dloads.
 Units are in inches [mm].



Slots	Width
3	4.12 in [105 mm]
4	5.12 in [130 mm]
5	6.12 in [155 mm]
6	7.12 in [181 mm]





Connect. Control. Optimize.



deltamotion.com

Printed in USA
June 2023

DELTA MOTION